

Gyratory Sieve Shaker, UMI-146-1

Sieve Shaker- Gyratory, For 20 & 30cm Dia Sieves With Digital Timer

Salient Features:

- Carries upto 7 sieves of either 200mm or 300mm diameter in single adaptor.
- The shaker is driven by a 1/4 HP motor through a reduction gear
- The sieve table does not rotate, but is inclined from the vertical axis.
- The direction of inclination changes progressively in clockwise direction.
- If the stop-pin below the table is removed, the shaker can have a rotary motion.
- In addition to this gyratory motion of the table, there is an upward and downward movement ensuring that each square cm of the sieve is utilized.
- A pair of rods and a holder is supplied along with the main unit.
- The holder can be fixed on top of the upper most sieves, and thus the sieve set is firmly held.
- Suitable for operation on 230 volts, 50 cycles single phase A.C. Supply.
- Fitted with Digital time switch adjustable from 1-99 minutes.
- Supplied without sieves or Lid-Pan



Technical Specification

- No. of sieves accommodated : 6 sieves + 1 set of Lid-Pan
- Make of the Motor : GODREJ LAWKIM
- No. of tapping from bottom : 85 to 90
- Timer : Digital - Pre-settable
- Timer Range : 0 TO 99 Minutes
- Power Supply : 220/230 Volts, 50 HZ, single Phase, AC